




Take Control In Speed



Varitron Engineering (Taiwan) Co., Ltd.

No.45, Lane171, Sec.1, Chung Shin Rd,

Wuku District, New Taipei City, Taiwan

新北市五股區中興路一段171巷45號

Tel : 886-2-29889598 Fax : 886-2-29850998

www.c-var.com

sales@c-var.com

Copyright Varitron Corporation. All Rights Reserved.

VARITRON

VARITRON[®]

Take Control In Speed

www.c-var.com

Cycloidal Speed Reducers



0.4 kW 1/2 HP	Hz	50Hz		60Hz	
	Pole	4	6	4	6
	n ₁	1450	980	1750	1165

50Hz					60Hz					Model 型號			Dimension Page 頁數							
Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out} N.m Kgf.m		Allowable Radial Load 應許徑向負載 Pro N r/min		SF	Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out} N.m Kgf.m		Allowable Radial Load 應許徑向負載 Pro N kgf		SF	Input Capacity Symbol 馬力 編號	Frame Size 框號	Ratio 速比	HM	VM	H	V		
	N	r/min	N	r/min			N	kgf	N	kgf										
242	15.0	1.53	1370	140	1.02	292	12.4	1.27	1290	132	1.02	05	8070	6						
			1920	196	1.95				1810	184	1.95								8080	6
			2860	292	2.88				2690	275	2.88								8090	6
181	20.0	2.04	1510	154	1.02	219	16.6	1.69	1430	145	1.02	05	8070	8						
			2080	212	1.95				1960	200	1.95								8080	8
			3190	326	2.88				3000	306	2.88								8090	8
132	27.5	2.81	1680	171	1.02	159	22.8	2.33	1590	162	1.02	05	8070	11						
			2300	234	1.95				2160	220	1.95								8080	11
			3340	340	2.88				3340	340	2.88								8090	11
112	32.5	3.32	1770	180	1.02	135	27.0	2.75	1680	171	1.02	05	8070	13						
			2470	251	1.48				2320	237	1.95								8080	13
			3340	340	2.88				3340	340	2.88								8090	13
96.7	37.5	3.83	1770	180	1.02	117	31.1	3.17	1680	171	1.02	05	8070	15						
			2550	260	1.95				2400	245	1.95								8080	15
			3340	340	2.88				3340	340	2.88								8090	15
85.3	42.5	4.34	1770	180	1.02	103	35.3	3.59	1770	180	1.02	05	8070	17						
			2560	261	1.95				2510	256	1.95								8080	17
			3340	340	2.88				3340	340	2.88								8090	17
69.0	52.6	5.36	2560	261	1.38	83.3	43.5	4.44	2450	250	1.38	05	8080	21						
			3340	340	1.90				3340	340	1.90								8090	21
58.0	62.6	6.38	2560	261	1.19	70.0	51.8	5.28	2520	256	1.19	05	8080	25						
			3340	340	2.17				3340	340	2.17								8090	25
50.0	72.6	7.40	2560	261	1.17	60.3	60.1	6.13	2560	261	1.17	05	8080	29						
			3340	340	1.96				3340	340	1.96								8090	29
41.4	87.6	8.93	2560	261	0.82	50.0	72.6	7.40	2560	261	0.93	05	8080	35						
			3340	340	1.90				3340	340	1.90								8090	35
			5400	550	3.00				5400	550	3.00								8105	35
33.7	108	11.0	3340	340	1.51	40.7	89.2	9.09	3340	340	1.51	05	8090	43						
			5400	550	2.70				5400	550	2.70								8105	43
28.4	128	13.0	3320	339	1.02	34.3	106	10.8	3340	340	1.06	05	8090	51						
			5400	550	1.94				5400	550	1.94								8105	51
24.6	148	15.1	3300	336	0.84	29.7	122	12.5	3340	340	0.93	05	8090	59						
			5400	550	1.70				5400	550	1.77								8105	59
			9810	1000	3.42				9810	1000	3.60								8125	59
20.4	178	18.1	5400	550	1.27	24.6	147	15.0	5400	550	1.09	05	8105	71						
			9810	1000	2.85				9810	1000	3.00								8120	71
16.7	218	22.2	5400	550	1.26	20.1	180	18.4	5400	550	1.41	05	8105	87						
			9810	1000	2.58				9810	1000	2.83								8125	87
13.9	247	25.1	5400	550	1.07	16.8	204	20.8	5400	550	1.07	05	8105DA	104						
			9810	1000	2.55				9810	1000	3.08		8125DB	104						
12.0	287	29.2	5400	550	1.07	14.5	238	24.2	5400	550	1.07	05	8105DA	121						
			9810	1000	2.17				9810	1000	2.62		8120DB	121						
			14700	1500	2.72				14700	1500	3.28		8135DB	121						
10.1	339	34.6	5400	550	0.88	12.2	281	28.6	5400	550	1.07	05	8105DA	143						
			9810	1000	1.07				9810	1000	1.07		8125DA	143						
			9810	1000	1.86				9810	1000	2.24		8125DB	143						
			14700	1500	2.77				14700	1500	3.35		8135DB	143						
8.79	391	39.9	9810	1000	1.07	10.6	324	33.0	9810	1000	1.07	05	8125DA	165						
			9810	1000	1.61				9810	1000	1.94		8125DB	165						
			14700	1500	2.40				14700	1500	2.90		8135DB	165						

0.4 kW 1/2 HP	Hz	50Hz		60Hz	
	Pole	4	6	4	6
	n ₁	1450	980	1750	1165

50Hz					60Hz					Model 型號			Dimension Page 頁數					
Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out} N.m Kgf.m		Allowable Radial Load 應許徑向負載 Pro N kgf		SF	Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out} N.m Kgf.m		Allowable Radial Load 應許徑向負載 Pro N kgf		SF	Input Capacity Symbol 馬力 編號	Frame Size 框號	Ratio 速比	HM	VM	H	V
	N	Kgf	N	Kgf			N	Kgf	N	Kgf								
7.44	462	47.1	9810	1000	1.14	8.97	383	39.1	9810	1000	1.07	05	8125DA	195				
			9810	1000	1.36				9810	1000	1.64	05	8125DB	195				
			14700	1500	2.03				14700	1500	2.45	05	8135DB	195				
			16000	1630	2.94				16000	1630	3.54	05	8145DB	195				
6.28	548	55.8	9810	1000	1.07	7.58	454	46.3	9810	1000	1.07	05	8125DA	231				
			9810	1000	1.15				9810	1000	1.39	05	8125DB	231				
			14700	1500	1.72				14700	1500	2.70	05	8135DB	231				
			16000	1630	2.44				16000	1630	2.95	05	8145DB	231				
5.31	647	66.0	9810	1000	0.97	6.41	536	54.7	9810	1000	1.07	05	8125DA	273				
			9810	1000	0.97				9810	1000	1.17	05	8125DB	273				
			14700	1500	1.07				14700	1500	1.07	05	8135DA	273				
			14700	1500	1.45				14700	1500	1.75	05	8135DB	273				
			16000	1630	2.07				16000	1630	2.49	05	8145DB	273				
			22100	2250	2.71				22100	2250	3.27	05	8165DB	273				
4.55	756	77.1	9810	1000	0.83	5.49	627	63.9	9810	1000	1.01	05	8125DA	319				
			14700	1500	1.07				14700	1500	1.07	05	8135DA	319				
			14700	1500	1.24				14700	1500	1.50	05	8135DB	319				
			16000	1630	1.81				16000	1630	2.19	05	8145DB	319				
			22100	2250	2.78				22100	2250	3.35	05	8165DA	319				
3.85	894	91.1	16000	1630	1.07	4.64	741	75.5	16000	1630	1.07	05	8145DA	377				
			16000	1630	1.53				16000	1630	1.85	05	8145DB	377				
			22100	2250	2.35				22100	2250	2.84	05	8165DA	377				
			29500	3010	2.83				29500	3010	3.42	05	8175DA	377				
3.07	1120	114	14700	1500	0.84	3.70	929	94.7	14700	1500	1.01	05	8135DA	473				
			16000	1630	1.07				16000	1630	1.07	05	8145DA	473				
			16000	1630	1.22				16000	1630	1.47	05	8145DB	473				
			22100	2250	1.87				22100	2250	2.26	05	8165DA	473				
			29500	3010	2.81				29500	3010	3.39	05	8175DA	473				
2.94	1170	119	16000	1630	1.02	3.55	969	98.8	16000	1630	1.02	05	8145DA	493				
			16000	1630	1.17				16000	1630	1.41	05	8145DB	493				
			22100	2250	1.79				22100	2250	2.17	05	8165DA	493				
			29500	3010	2.69				29500	3010	3.25	05	8175DA	493				
			15900	1620	1.03				16000	1630	1.07	05	8145DA	559				
2.59	1330	135	15900	1620	1.03	3.13	1100	112	16000	1630	1.25	05	8145DB	559				
			22100	2250	1.58				22100	2250	1.91	05	8165DA	559				
			29500	3010	2.38				29500	3010	2.87	05	8175DA	559				
			16000	1630	0.89				16000	1630	1.07	05	8145DA	649				
2.23	1540	157	22100	2250	1.36	2.70	1280	130	22100	2250	1.65	05	8165DA	649				
			29500	3010	2.05				29500	3010	2.47	05	8175DA	649				
			22100	2250	1.21				22100	2250	1.46	05	8165DA	731				
1.98	1730	177	29500	3010	1.82	2.39	1440	146	29500	3010	2.19	05	8175DA	731				
			22100	2250	1.05				22100	2250	1.27	05	8165DA	841				
1.72	1990	203	29500	3010	1.58	2.08	1650	168	29500	3010	1.91	05	8175DA	841				
			22100	2250	0.88				22100	2250	1.07	05	8165DA	1003				
1.45	2380	242	29500	3010	1.06	1.74	1970	201	29500	3010	1.60	05	8175DA	1003				
			2100	214	*				2100	214	*	05	8165DA	1247				
1.16	2960	301	29500	3010	1.07	1.40	2450	250	29500	3010	1.29	05	8175DA	1247				
	2050	209	21800	2220	*				2050	209	21800	2220	*	05	8165DA	1479		
0.980	3510	357	29500	3010	0.90	1.18	2910	296	29500	3010	1.08	05	8175DA	1479				

0.4 kW 1/2 HP	Hz	50Hz		60Hz	
	Pole	4	6	4	6
	n ₁	1450	980	1750	1165

50Hz						60Hz						Model 型號			Dimension Page 頁數			
Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Input Capacity Symbol 馬力 編號	Frame Size 框號	Ratio 速比	HM	VM	H	V
	N.m	Kgf.m	N	kgf			N	kgf	N	kgf								
0.784	2100	214	22100	2250	*	0.946	2100	214	22100	2250	*	05	8165DA	1849				
	3150	321	29500	3010	*		3150	321	29500	3010	*	05	8175DA	1849				
	4380	447	41700	4250	0.93		3630	370	41700	4250	1.12	05	8185DA	1849				
0.702	3150	321	29500	3010	*	0.847	3150	321	29500	3010	*	05	8175DA	2065				
	4050	413	41700	4250	*		4050	413	41700	4250	*	05	8185DA	2065				
0.572	3150	321	29500	3010	*	0.690	3150	321	29500	3010	*	05	8175DA	2537				
	6020	613	41200	4200	0.83		4980	508	41600	4240	1.00	05	8185DA	2537				
0.476	5000	510	41700	4250	*	0.575	5000	510	41700	4250	*	05	8185DA	3045				
0.417	5000	510	41600	4240	*	0.503	5000	510	41600	4240	*	05	8185DA	3481				
0.327	5000	510	41700	4250	*	0.394	5000	510	41700	4250	*	05	8185DA	4437				
0.282	5000	510	41700	4250	*	0.341	5000	510	41700	4250	*	05	8185DA	5133				
0.235	5000	510	41700	4250	*	0.283	5000	510	41700	4250	*	05	8185DA	6177				
0.192	5000	510	41700	4250	*	0.231	5000	510	41700	4250	*	05	8185DA	7569				

0.75 kW 1 HP	Hz	50Hz		60Hz	
	Pole	4	6	4	6
	n ₁	1450	980	1750	1165

50Hz						60Hz						Model 型號			Dimension Page 頁數			
Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Input Capacity Symbol 馬力 編號	Frame Size 框號	Ratio 速比	HM	VM	H	V
	N.m	Kgf.m	N	kgf			N	kgf	N	kgf								
242	28.2	2.87	1900	193	1.04	292	23.3	2.38	1790	182	1.04	1	8080	6				
			2840	290	2.03				2670	273	2.03				1	8090	6	
181	37.5	3.83	2050	209	1.04	219	31.1	3.17	1930	197	1.04	1	8080	8				
			3160	322	2.03				2980	304	2.03				1	8090	8	
132	51.6	5.26	2250	230	1.04	159	42.8	4.36	2130	217	1.04	1	8080	11				
			3340	340	2.03				3340	340	2.03				1	8090	11	
112	61.0	5.22	2410	246	1.04	135	50.5	5.15	2280	233	1.04	1	8080	13				
			3340	340	2.03				3340	340	2.03				1	8090	13	
96.7	70.4	7.18	2490	253	1.04	117	58.3	5.95	2350	240	1.04	1	8080	15				
			3340	340	2.03				3340	340	2.03				1	8090	15	
85.3	79.8	8.13	2560	261	1.04	103	66.1	6.74	2460	251	1.04	1	8080	17				
			3340	340	2.03				3340	340	1.53				1	8090	17	
			5400	550	2.65				5400	550	2.03				1	8105	17	
69.0	98.5	10.0	3340	340	2.01	83.3	81.7	8.32	3340	340	1.01	1	8090	21				
			5400	550	2.53				5400	550	2.57				1	8105	21	
58.0	117	12.0	3340	340	1.15	70.0	97.2	9.91	3340	340	1.15	1	8090	25				
			5400	550	2.23				5400	550	2.23				1	8105	25	
50.0	136	13.9	3320	338	1.05	60.3	113	11.5	3340	340	1.05	1	8090	29				
			5400	550	2.12				5400	550	2.12				1	8105	29	

0.75 kW 1 HP	Hz	50Hz		60Hz	
	Pole	4	6	4	6
	n ₁	1450	980	1750	1165

50Hz						60Hz						Model 型號			Dimension Page 頁數			
Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Input Capacity Symbol 馬力 編號	Frame Size 框號	Ratio 速比	HM	VM	H	V
	N.m	Kgf.m	N	kgf			N.m	Kgf.m	N	kgf								
41.4	164	16.7	3270	334	1.01	50.0	136	13.9	3330	339	1.01	1	8090	35				
			5400	550	1.60				5400	550	1.60		1	8105	35			
33.7	202	20.6	3210	328	0.80	40.7	167	17.0	3280	334	0.80	1	8090	43				
			5400	550	1.44				5400	550	1.44		1	8105	43			
			9810	1000	2.55				9640	983	2.55		1	8125	43			
28.4	239	24.4	5400	550	1.03	34.3	198	20.2	5390	549	1.03	1	8105	51				
			9810	1000	2.63				9810	1000	3.04		1	8125	51			
24.6	277	28.2	5400	550	0.91	29.7	229	23.4	5370	548	0.94	1	8105	59				
			9810	1000	1.73				9810	1000	2.16		1	8125	59			
			13200	1340	2.81				12400	1270	2.92		1	8135	59			
20.4	333	34.0	9810	1000	1.52	24.6	276	28.1	9810	1000	1.60	1	8125	71				
			14000	1420	2.71				13100	1340	2.89		1	8135	71			
16.7	408	41.6	9810	1000	1.37	20.1	338	34.5	9810	1000	1.51	1	8125	87				
			14700	1500	2.20				14200	1440	2.55		1	8135	87			
			16000	1630	2.88				16000	1630	3.31		1	8145	87			
13.9	462	47.1	9810	1000	1.36	16.8	383	39.1	9810	1000	1.64	1	8125DB	104				
			14700	1500	2.03				14700	1500	2.13		1	8135DB	104			
			14700	1500	2.03				14700	1500	2.45		1	8135DC	104			
			16000	1630	2.13				16000	1630	2.13		1	8145DB	104			
			16000	1630	2.96				16000	1630	3.58		1	8145DC	104			
12.0	538	54.8	9810	1000	1.16	14.5	446	45.4	9810	1000	1.40	1	8125DB	121				
			14700	1500	1.75				14700	1500	2.11		1	8135DB	121			
			16000	1630	2.13				16000	1630	2.13		1	8145DB	121			
			16000	1630	2.40				16000	1630	2.90		1	8145DC	121			
10.1	636	64.8	9810	1000	0.98	12.2	527	53.7	9810	1000	1.20	1	8125DB	143				
			14700	1500	1.48				14700	1500	1.78		1	8135DB	143			
			16000	1630	2.13				16000	1630	2.13		1	8145DB	143			
			16000	1630	2.15				16000	1630	2.60		1	8145DC	143			
			22100	2250	2.76				22100	2250	3.33		1	8165DB	143			
8.79	734	74.8	9810	1000	0.86	10.6	608	62.0	9810	1000	1.04	1	8125DB	165				
			14700	1500	1.28				14700	1500	1.55		1	8135DB	165			
			16000	1630	1.85				16000	1630	2.13		1	8145DB	165			
			16000	1630	1.85				16000	1630	2.23		1	8145DC	165			
			22100	2250	2.13				22100	2250	2.13		1	8165DA	165			
			22100	2250	2.86				22100	2250	3.46		1	8165DB	165			
7.44	867	88.4	14700	1500	1.08	8.97	718	73.2	14700	1500	1.31	1	8135DB	195				
			16000	1630	1.57				16000	1630	1.89		1	8145DB	195			
			22100	2250	2.13				22100	2250	2.13		1	8165DA	195			
			22100	2250	2.42				22100	2250	2.92		1	8165DB	195			
			29500	3010	2.92				29500	3010	3.52		1	8175DB	195			
6.28	1030	105	14700	1500	0.92	7.58	851	86.7	14700	1500	1.10	1	8135DB	231				
			16000	1630	1.30				16000	1630	1.57		1	8145DB	231			
			22100	2250	2.04				22100	2250	2.13		1	8165DA	231			
			22100	2250	2.04				22100	2250	2.47		1	8165DB	231			
			29500	3010	2.13				29500	3010	2.13		1	8175DA	231			
			29500	3010	2.46				29500	3010	2.97		1	8175DB	231			
5.31	1210	124	16000	1630	1.10	6.41	1010	103	16000	1630	1.33	1	8145DB	273				
			22100	2250	1.73				22100	2250	2.09		1	8165DA	273			
			29500	3010	2.13				29500	3010	2.13		1	8175DA	273			
			29500	3010	2.60				29500	3010	3.13		1	8175DB	273			

0.75 kW 1 HP	Hz	50Hz		60Hz	
	Pole	4	6	4	6
	n ₁	1450	980	1750	1165

50Hz						60Hz						Model 型號			Dimension Page 頁數			
Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Input Capacity Symbol 馬力 編號	Frame Size 框號	Ratio 速比	HM	VM	H	V
	N.m	Kgf.m	N	kgf			N.m	Kgf.m	N	kgf								
4.55	1420	145	15500	1580	0.97	5.49	1180	120	16000	1630	1.17	1	8145DB	319				
			22100	2250	1.48				22100	2250	1.79		8165DA	319				
			29500	3010	2.13				29500	3010	2.13		8175DA	319				
			29500	3010	2.22				29500	3010	2.68		8175DB	319				
			41700	4250	2.86				41700	4250	3.45		8185DA	319				
3.85	1680	171	14100	1440	0.82	4.64	1390	142	15700	1600	0.98	1	8145DB	377				
			22100	2250	1.25				22100	2250	1.51		8165DA	377				
			29500	3010	1.88				29500	3010	2.13		8175DA	377				
			29500	3010	1.88				29500	3010	2.27		8175DB	377				
			41700	4250	2.98				41700	4250	3.60		8185DA	377				
3.07	1370	140	15800	1600	*	3.70	1370	140	15700	1600	*	1	8145DB	473				
	2100	214	22100	2250	1.00		1740	178	22100	2250	1.21		8165DA	473				
			29500	3010	1.50				29500	3010	1.81		8175DA	473				
			41700	4250	2.38				41700	4250	2.87		8185DA	473				
2.94	2190	223	15800	1610	*	3.55	1820	186	15800	1610	*	1	8145DB	493				
			22100	2250	0.96				22100	2250	1.15		8165DA	493				
			29500	3010	1.44				29500	3010	1.73		8175DA	493				
			41700	4250	2.28				41700	4250	2.75		8185DA	493				
			59000	6010	2.91				59000	6010	3.51		8195DA	493				
2.59	2490	253	22100	2250	0.85	3.13	2060	210	22100	2250	1.02	1	8165DA	559				
			29500	3010	1.27				29500	3010	1.53		8175DA	559				
			41700	4250	2.01				41700	4250	2.43		8185DA	559				
			59000	6010	2.57				59000	6010	3.10		8195DA	559				
2.23	2100	214	22100	2250	*	2.70	2100	214	22100	2250	*	1	8165DA	649				
	2890	294	29500	3010	1.09		2390	244	29500	3010	1.32		8175DA	649				
			41700	4250	1.73				41700	4250	2.09		8185DA	649				
			59000	6010	2.76				59000	6010	3.33		8195DA	649				
1.98	3250	331	22100	2250	*	2.39	2690	274	22100	2250	*	1	8165DA	731				
			29500	3010	0.97				29500	3010	1.17		8175DA	731				
			41700	4250	1.54				41700	4250	1.86		8185DA	731				
			59000	6010	2.45				59000	6010	2.96		8195DA	731				
1.72	3740	381	29500	3010	0.84	2.08	3100	316	29500	3010	1.02	1	8175DA	841				
			41700	4250	1.34				41700	4250	1.61		8185DA	841				
			59000	6010	2.13				59000	6010	2.57		8195DA	841				
1.45	3150	321	29500	3010	*	1.74	3150	321	29500	3010	*	1	8175DA	1003				
	4460	455	41700	4250	1.12		3690	377	41700	4250	1.35		8185DA	1003				
			59000	6010	1.79				59000	6010	2.15		8195DA	1003				
1.16	5540	565	41700	4250	0.90	1.40	4590	468	41700	4250	1.09	1	8185DA	1247				
			59000	6010	1.44				59000	6010	1.73		8195DA	1247				
0.980	5000	510	41700	4250	*	1.18	5000	510	41700	4250	*	1	8185DA	1479				
	6580	670	58800	5990	1.21		5450	555	59000	6010	1.46		8195DA	1479				
0.784	5000	510	59000	6010	*	0.946	5000	510	41700	4250	*	1	8185DA	1849				
	8220	838	58900	6000	0.97		6810	694	59000	6010	1.17		8195DA	1849				
0.702	5000	510	41600	4240	*	0.847	5000	510	41600	4240	*	1	8185DA	2065				
	9180	936	57800	5890	0.87		7610	775	58200	5940	1.05		8195DA	2065				
0.572	7960	811	58100	5930	*	0.690	7960	811	58100	5930	*	1	8195DA	2537				
	11300	1150	84100	8570	0.82		9350	953	84100	8570	1.00		8205DA	2537				
0.476	7960	811	85400	5950	*	0.575	7960	811	58400	5950	*	1	8195DA	3045				
	8760	893	84100	8570	*		8760	893	84100	8570	*		8205DA	3045				
0.417	7960	811	58100	5930	*	0.503	7960	811	58100	5930	*	1	8195DA	3481				
	9300	948	84100	8570	*		9300	948	84100	8570	*		8205DA	3481				

0.75 kW 1 HP	Hz	50Hz		60Hz	
	Pole	4	6	4	6
	n ₁	1450	980	1750	1165

50Hz						60Hz						Model 型號			Dimension Page 頁數			
Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Input Capacity Symbol 馬力 編號	Frame Size 框號	Ratio 速比	HM	VM	H	V
	N.m	Kgf.m	N	kgf			N	kgf	N	kgf								
0.327	7960	811	58400	5950	*	0.394	7960	811	58400	5950	*	1	8195DA	4437				
	8760	893	84100	8570	*		8760	893	84100	8570	*	1	8205DA	4437				
0.282	7960	811	58400	5950	*	0.341	7960	811	58400	5950	*	1	8195DA	5133				
	9300	948	84100	8570	*		9300	948	84100	8570	*	1	8205DA	5133				
0.235	7960	811	58400	5950	*	0.283	7960	811	58400	5950	*	1	8195DA	6177				
	8760	893	84100	8570	*		8760	893	84100	8570	*	1	8205DA	6177				
0.192	7960	811	58400	5950	*	0.231	7960	811	58400	5950	*	1	8195DA	7569				
	8760	893	84100	8570	*		8760	893	84100	8570	*	1	8205DA	7539				

1.5 kW 2 HP	Hz	50Hz		60Hz	
	Pole	4	6	4	6
	n ₁	1450	980	1750	1165

50Hz						60Hz						Model 型號			Dimension Page 頁數				
Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Input Capacity Symbol 馬力 編號	Frame Size 框號	Ratio 速比	HM	VM	H	V	
	N.m	Kgf.m	N	kgf			N	kgf	N	kgf									
242	56.3	5.74	4130	421	2.12	292	46.7	4.76	3880	396	2.12	2	8105	6					
181	75.1	7.65	4600	469	2.12	219	62.2	6.34	4330	441	2.12	2	8105	8					
132	103	10.5	5220	532	2.12	159	85.5	8.72	4920	501	2.12	2	8105	11					
112	122	12.4	5400	550	2.12	135	101	10.3	5110	521	2.12	2	8105	13					
96.7	141	14.4	5400	550	2.12	117	117	11.9	5400	550	2.12	2	8105	15					
85.3	160	16.3	5400	550	1.64	103	132	13.5	5400	550	1.64	2	8105	17					
69.0	197	20.1	5400	550	1.52	83.3	163	16.6	5400	550	1.56	2	8105	21					
			8260	842	2.64				7780	793	2.64		2	8125	21				
58.0	235	23.9	5400	550	1.11	70.0	194	19.8	5400	550	1.11	2	8105	25					
			8650	882	2.64				8150	831	2.64		2	8125	25				
50.0	272	27.7	5400	550	1.06	60.3	226	23.0	5400	550	1.06	2	8105	29					
			8990	916	2.31				8470	863	2.51		2	8125	29				
			10500	1070	2.87				9920	1010	2.99		2	8135	29				
41.4	328	33.5	4820	491	0.80	50.0	272	27.7	5330	544	0.80	2	8105	35					
			9490	967	1.92				8940	912	2.12		2	8125	35				
			11100	1130	2.74				10400	1060	2.83		2	8135	35				
33.7	404	41.1	9810	1000	1.56	40.7	334	34.1	9510	969	1.59	2	8125	43					
			11900	1210	2.23				11200	1140	2.51		2	8135	43				
			16000	1630	2.63				15900	1620	2.63		2	8145	43				
28.4	479	48.8	9810	1000	1.31	34.3	397	40.4	9810	1000	1.15	2	8125	51					
			12400	1260	1.70				11700	1190	1.95		2	8135	51				
			16000	1630	2.47				16000	1630	2.81		2	8145	51				
24.6	554	56.4	9810	1000	1.08	29.7	459	46.8	9810	1000	1.08	2	8125	59					
			13000	1320	1.63				12200	1250	1.68		2	8135	59				
			16000	1630	2.12				16000	1630	2.43		2	8145	59				
			22100	2250	2.95				22100	2250	2.95		2	8165	59				

1.5 kW 2 HP	Hz	50Hz		60Hz	
	Pole	4	6	4	6
	n ₁	1450	980	1750	1165

50Hz					60Hz					Model 型號			Dimension Page 頁數					
Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Input Capacity Symbol 馬力 編號	Frame Size 框號	Ratio 速比	HM	VM	H	V
	N.m	Kgf.m	N	kgf			N.m	Kgf.m	N	kgf								
20.4	666	67.9	13700	1400	1.35	24.6	552	56.3	12900	1320	1.45	2	8135	71				
			16000	1630	1.75				16000	1630	2.02		8145	71				
			22100	2250	2.31				22100	2250	2.31		8165	71				
16.7	817	83.2	14700	1500	1.10	20.1	677	69.0	13900	1420	1.27	2	8135	87				
			16000	1630	1.44				16000	1630	1.65		8145	87				
			22100	2250	2.51				22100	2250	2.60		8165	87				
13.9	925	94.3	14700	1500	1.02	16.8	766	78.1	14700	1500	1.23	2	8135DC	104				
			16000	1630	1.48				16000	1630	1.79		8145DC	104				
			22100	2250	2.24				22100	2250	2.24		8165DB	104				
			22100	2250	2.27				22100	2250	2.74		8165DC	104				
			29500	3010	2.73				29500	3010	3.30		8175DC	104				
12.0	1080	110	16000	1630	1.20	14.5	891	90.9	16000	1630	1.45	2	8145DC	121				
			22100	2250	1.63				22100	2250	1.97		8165DB	121				
			22100	2250	1.95				22100	2250	2.36		8165DC	121				
			29500	3010	2.24				29500	3010	2.24		8175DB	121				
			29500	3010	2.93				29500	3010	3.53		8175DC	121				
10.1	940	95.8	14700	1500	*	12.2	940	95.8	14700	1500	*	2	8135DC	143				
	1270	130	16000	1630	1.08				16000	1630	1.30		8145DC	143				
			22100	2250	1.65				22100	2250	1.99		8165DB	143				
			29500	3010	2.24				29500	3010	2.24		8175DB	143				
			29500	3010	2.48				29500	3010	2.99		8175DC	143				
8.79	1470	150	15500	1580	0.93	10.6	1220	124	16000	1630	1.07	2	8140DC	165				
			22100	2250	1.43				22100	2250	1.73		8165DB	165				
			29500	3010	2.15				29500	3010	2.24		8175DB	165				
			41700	4250	2.24				41700	4250	2.24		8185DA	165				
			41700	4250	2.77				41700	4250	3.34		8185DB	165				
7.44	1360	138	16000	1630	*	8.97	1360	138	16000	1630	*	2	8145DC	195				
	1730	177	22100	2250	1.21				22100	2250	1.46		8165DB	195				
			29500	3010	1.82				29500	3010	2.19		8175DB	195				
			41700	4250	2.12				41700	4250	2.24		8185DA	195				
			41700	4250	2.84				41700	4250	3.43		8185DB	195				
6.28	2050	209	22100	2250	1.02	7.58	1700	173	22100	2250	1.23	2	8165DB	231				
			29500	3010	1.53				29500	3010	1.85		8175DB	231				
			41700	4250	2.12				41700	4250	2.12		8185DA	231				
			41700	4250	2.43				41700	4250	2.94		8185DB	231				
			22100	2250	0.87				22100	2250	1.04		8165DB	273				
5.31	2430	247	29500	3010	1.30	6.41	2010	205	29500	3010	1.57	2	8175DB	273				
			41700	4250	2.06				41700	4250	2.24		8185DA	273				
			41700	4250	2.06				41700	4250	2.49		8185DB	273				
			59000	6010	2.63				59000	6010	3.17		8195DA	273				
			2100	214	22100				2250	*	5.49		2100	214	22100	2250	*	2
2840	289	29500	3010	1.11	29500	3010	1.34	8175DB	319									
		41700	4250	1.76	41700	4250	2.13	8185DA	319									
		59000	6010	2.81	59000	6010	3.39	8195DA	319									
3.85	2100	214	22100	2250	*	4.64	2100	214	22100	2250	*	2	8165DB	377				
	3350	342	29500	3010	0.94				29500	3010	1.07		8175DB	377				
			41700	4250	1.49				41700	4250	1.80		8185DA	377				
			59000	6010	2.37				59000	6010	2.87		8195DA	377				
3.07	3150	321	29500	3010	*	3.70	3150	321	29500	3010	*	2	8175DB	473				
	4210	429	41700	4250	1.19				41700	4250	1.43		8185DA	473				
			59000	6010	1.89				59000	6010	2.28		8195DA	473				

1.5 kW 2 HP	Hz	50Hz		60Hz	
	Pole	4	6	4	6
	n ₁	1450	980	1750	1165

50Hz						60Hz						Model 型號			Dimension Page 頁數			
Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Input Capacity Symbol 馬力 編號	Frame Size 框號	Ratio 速比	HM	VM	H	V
	N.m	Kgf.m	N	kgf			N.m	Kgf.m	N	kgf								
2.94	3150	321	29500	3010	*	3.55	3150	321	29500	3010	*	2	8175DB	493				
	4380	446	41700	4250	1.14		3630	370	41700	4250	1.38	2	8185DA	493				
			59000	6010	1.82				59000	6010	2.19	2	8195DA	493				
2.59	3150	321	29500	3010	*	3.13	3150	321	29500	3010	*	2	8175DB	559				
			41700	4250	1.01		4120	420	41700	4250	1.21	2	8185DA	559				
			59000	6040	1.60				59000	6040	1.93	2	8195DA	559				
2.23	3150	321	29500	3010	*	2.70	3150	321	29500	3010	*	2	8175DB	649				
	5770	588	41300	4210	0.87		4780	487	41700	4250	1.05	2	8185DA	649				
			58700	5990	1.38				59000	6010	1.66	2	8195DA	649				
1.98	5000	510	41700	4250	*	2.39	5000	510	41700	4250	*	2	8185DA	731				
	6500	663	59000	6010	1.22		5390	549	59000	6010	1.48	2	8195DA	731				
1.72	5000	510	41700	4250	*	2.08	5000	510	41700	4250	*	2	8185DA	841				
	7480	762	59000	6010	1.06		6200	632	59000	6010	1.28	2	8195DA	841				
1.45	5000	510	41700	4250	*	1.74	5000	510	41700	4250	*	2	8185DA	1003				
	8920	909	57900	5900	0.89		7390	753	58300	5940	1.08	2	8195DA	1003				
1.16	7960	811	59000	6010	*	1.40	7960	811	59000	6010	*	2	8195DA	1247				
	8760	893	84100	8570	*		8360	853	84100	8570	*	2	8205DA	1247				
0.980	8760	893	84100	8570	*	1.18	8360	853	84100	8570	*	2	8205DA	1479				
	13200	1340	104000	10600	0.86		10900	1100	104000	10600	1.03	2	8215DA	1479				
0.784	9300	948	84100	8570	*	0.946	9300	948	84100	8570	*	2	8205DA	1849				
	12700	1290	104000	10600	*		12700	1290	104000	10600	*	2	8215DA	1849				
	16400	1680	145000	14800	0.97		13600	1390	145000	14800	*	2	8225DA	1849				
0.702	9300	948	84100	8570	*	0.847	9300	948	84100	8570	*	2	8205DA	2065				
	12700	1290	104000	10600	*		12700	1290	104000	10600	*	2	8215DA	2065				
	18400	1870	145000	14800	0.86		15200	1500	145000	14800	1.04	2	8225DA	2065				
0.572	12700	1290	104000	10600	*	0.690	12700	1290	104000	10600	*	2	8215DA	3045				
	15900	1620	145000	14800	*		15900	1620	145000	14800	*	2	8225DA	3045				
0.476	11300	1150	104000	10600	*	0.575	11300	1150	104000	10600	*	2	8215DA	3045				
	15100	1540	145000	14800	*		15100	1540	145000	14800	*	2	8225DA	3045				
0.417	12700	1290	104000	10600	*	0.503	12700	1290	104000	10600	*	2	8215DA	3481				
	15900	1620	145000	14800	*		15900	1620	145000	14800	*	2	8225DA	3481				
0.327	11300	1150	104000	10600	*	0.394	11300	1150	104000	10600	*	2	8215DA	4437				
	15100	1540	145000	14800	*		15100	1540	145000	14800	*	2	8225DA	4437				
0.282	12700	1290	104000	10600	*	0.341	12700	1290	104000	10600	*	2	8215DA	5133				
	15900	1620	145000	14800	*		15900	1620	145000	14800	*	2	8225DA	5133				
0.235	11300	1150	104000	10600	*	0.283	11300	1150	104000	10600	*	2	8215DA	6177				
	15100	1540	145000	14800	*		15100	1540	145000	14800	*	2	8225DA	6177				
0.192	11300	1150	104000	10600	*	0.231	11300	1150	104000	10600	*	2	8215DA	7569				
	15100	1540	145000	14800	*		15100	1540	145000	14800	*	2	8225DA	7569				

2.2 kW 3 HP	Hz	50Hz		60Hz	
	Pole	4	6	4	6
	n ₁	1450	980	1750	1165

50Hz						60Hz						Model 型號			Dimension Page 頁數			
Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Input Capacity Symbol 馬力 編號	Frame Size 框號	Ratio 速比	HM	VM	H	V
	N.m	Kgf.m	N	kgf			N.m	Kgf.m	N	kgf								
242	82.6	8.42	4090	417	1.45	292	68.4	6.98	3860	393	1.45	3	8105	6				
			5260	536	2.30				4950	505	2.30		8125	6				
181	110	11.2	4560	465	1.45	219	91.2	9.30	4300	438	1.45	3	8105	8				
			5870	598	2.30				5520	563	2.30		8125	8				
132	151	15.4	5170	527	1.45	159	125	12.8	4870	497	1.45	3	8105	11				
			6670	680	2.69				6280	640	2.69		8125	11				
112	179	18.2	5360	547	1.45	135	148	15.1	5060	516	1.45	3	8105	13				
			6890	702	2.69				6490	662	2.69		8125	13				
96.7	206	21.0	5400	550	1.45	117	171	17.4	5340	544	1.45	3	8105	15				
			7390	753	2.69				6960	710	2.69		8125	15				
85.3	234	23.9	5400	550	1.12	103	194	19.8	5400	550	1.12	3	8105	17				
			7460	760	2.57				7030	716	2.57		8125	17				
69.0	289	29.5	5400	550	1.04	83.3	240	24.4	5400	550	1.06	3	8105	21				
			8180	834	2.18				7710	786	2.22		8125	21				
			9580	976	2.70				9020	919	2.79		8135	21				
58.0	344	35.1	8560	873	1.80	70.0	285	29.1	8070	823	1.80	3	8125	25				
			9950	1010	2.61				9370	955	2.70		8135	25				
50.0	399	40.7	8880	905	1.58	60.3	331	33.7	8380	854	1.71	3	8125	29				
			10500	1070	2.22				9850	1000	2.56		8135	29				
			15000	1530	2.70				14200	1450	2.70		8145	29				
41.4	482	49.1	9350	954	1.08	50.0	399	40.7	8830	900	1.13	3	8125	35				
			11000	1120	1.87				10300	1050	1.93		8135	35				
			16000	1630	2.85				15200	1550	3.42		8145	35				
33.7	592	60.3	9810	1000	1.06	40.7	490	50.0	9380	956	1.08	3	8125	43				
			11800	1200	1.52				11100	1130	1.71		8135	43				
			16000	1630	2.12				15900	1620	2.45		8145	43				
			20600	2100	2.93				19300	1970	3.39		8165	43				
28.4	702	71.6	9810	1000	0.90	34.3	582	59.3	9760	995	1.04	3	8125	51				
			12200	1250	1.16				11500	1180	1.33		8135	51				
			16000	1630	1.68				16000	1630	1.92		8145	51				
			21300	2180	2.99				20100	2050	3.42		8165	51				
24.6	812	82.8	12800	1300	1.11	29.7	673	68.6	12100	1230	1.15	3	8135	59				
			16000	1630	1.45				16000	1630	1.66		8145	59				
			22100	2250	2.59				22100	2250	2.61		8165	59				
20.4	977	99.6	13500	1380	0.92	24.6	810	82.5	12800	1300	0.98	3	8135	71				
			16000	1630	1.19				16000	1630	1.38		8145	71				
			22100	2250	2.15				22100	2250	2.57		8165	71				
16.7	1200	122	16000	1630	0.98	20.1	992	101	16000	1630	1.13	3	8145	87				
			22100	2250	1.71				22100	2250	1.77		8165	87				
13.9	940	95.8	14700	1500	*	16.8	940	95.8	14700	1500	*	3	8135DC	104				
			16000	1630	1.01				16000	1630	1.22		8145DC	104				
	1360	138	22100	2250	1.53		22100	2250	1.53	8165DB	104							
			22100	2250	1.55		22100	2250	1.87	8165DC	104							
			29500	3010	2.32		29400	3000	2.80	8175DC	104							
			41300	4210	2.99		38800	3960	3.61	8185DB	104							
12.0	1580	161	15300	1560	0.82	14.5	1310	133	16000	1630	0.98	3	8145DC	121				
			22100	2250	1.33				22100	2250	1.53		8165DB	121				
			22100	2250	1.33				22100	2250	1.61		8165DC	121				
			29500	3010	1.53				29500	3010	1.53		8175DB	121				
			29500	3010	2.00				29500	3010	2.41		8175DC	121				
			41700	4250	2.57				41300	4210	3.11		8185DB	121				

2.2 kW 3 HP	Hz	50Hz		60Hz	
	Pole	4	6	4	6
	n ₁	1450	980	1750	1165

50Hz					60Hz					Model 型號			Dimension Page 頁數					
Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Input Capacity Symbol 馬力 編號	Frame Size 框號	Ratio 速比	HM	VM	H	V
	N.m	Kgf.m	N	kgf			N.m	Kgf.m	N	kgf								
0.572	20500	2090	179000	18200	*	0.690	20500	2090	179000	18200	*	3	8235DA	2537				
	25800	2630	208000	21200	*		25800	2630	208000	21200	*	3	8245DA	2537				
0.476	17200	1750	179000	18200	*	0.575	17200	1750	179000	18200	*	3	8234DA	3045				
	22600	2310	208000	21200	*		22600	2310	208000	21200	*	3	8245DA	3045				
0.417	20500	2090	179000	18200	*	0.503	20500	2090	179000	18200	*	3	8235DA	3481				
	25800	2630	208000	21200	*		25800	2630	208000	21200	*	3	8245DA	3481				
0.327	17200	1750	179000	18200	*	0.394	17200	1750	179000	18200	*	3	8235DA	4437				
	22600	2310	208000	21200	*		22600	2310	208000	21200	*	3	8245DA	4437				
0.282	20500	2090	179000	18200	*	0.341	20500	2090	179000	18200	*	3	8234DA	5133				
	25800	2630	208000	21200	*		25800	2630	208000	21200	*	3	8245DA	5133				
0.235	17200	1750	179000	18200	*	0.283	17200	1750	179000	18200	*	3	8234DA	6177				
	22600	2310	208000	21200	*		22600	2310	208000	21200	*	3	8245DA	6177				
0.192	17200	1750	179000	18200	*	0.231	17200	1750	179000	18200	*	3	8235DA	7569				
	22600	2310	208000	21200	*		22600	2310	208000	21200	*	3	8245DA	7569				

3.7 kW 5 HP	Hz	50Hz		60Hz	
	Pole	4	6	4	6
	n ₁	1450	980	1750	1165

50Hz					60Hz					Model 型號			Dimension Page 頁數								
Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Input Capacity Symbol 馬力 編號	Frame Size 框號	Ratio 速比	HM	VM	H	V			
	N.m	Kgf.m	N	kgf			N.m	Kgf.m	N	kgf											
242	139	14.2	5210	531	1.88	292	115	11.7	4320	440	1.06	5	8125	6							
			6120	624	2.54				5760	587	2.54				5	8135	6				
181	185	18.9	5800	591	1.88	219	153	15.6	5470	557	1.88	5	8125	8							
			6820	695	2.54				6420	655	2.54				5	8135	8				
132	255	26.0	6580	670	1.60	159	211	21.5	6200	632	1.60	5	8125	11							
			7770	792	2.54				7320	746	2.54				5	8135	11				
112	301	30.7	6780	824	1.60	135	249	25.4	6400	652	1.60	5	8125	13							
			8080	824	2.54				7620	776	2.54				5	8135	13				
96.7	347	35.4	7260	741	1.60	117	288	29.3	6860	699	1.60	5	8125	15							
			8250	841	2.42				7770	792	2.42				5	8135	15				
85.3	394	40.1	7320	747	1.53	103	326	33.2	6920	705	1.53	5	8125	17							
			8850	902	2.24				8340	850	2.24				5	8135	17				
69.0	486	49.6	13100	1330	2.73	83.3	403	41.1	12300	1260	2.73	5	8145	17							
			8010	816	1.29				7570	772	1.32				5	8125	21				
58.0	579	59.0	9440	962	1.82	70.0	480	48.9	8900	908	2.04	5	8135	21							
			14000	1420	2.56				13200	1350	2.97				5	8145	21				
58.0	579	59.0	8350	851	1.07	70.0	480	48.9	7900	806	1.07	5	8125	25							
			9790	998	1.55				9240	942	1.61				5	8135	25				
			14600	1490	2.14				13800	1410	2.14				5	8145	25				
			17200	1760	2.66				16200	1650	2.66				5	8165	25				

3.7 kW 5 HP	Hz	50Hz		60Hz	
	Pole	4	6	4	6
	n ₁	1450	980	1750	1165

50Hz						60Hz						Model 型號			Dimension Page 頁數			
Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out} N.m / Kgf.m		Allowable Radial Load 應許徑向負載 Pro N / kgf		SF	Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out} N.m / Kgf.m		Allowable Radial Load 應許徑向負載 Pro N / kgf		SF	Input Capacity Symbol 馬力編號	Frame Size 框號	Ratio 速比	HM	VM	H	V
6.28	5070	516	41700	4250	0.98	7.58	4200	428	41700	4250	1.19	5	8185DB	231				
			59000	6010					59000	6010								
			59000	6010					59000	6010								
			84100	8570					84100	8570								
			104000	10600					104000	10600								
			140000	14200					132000	13500								
			140000	14200					132000	13500								
5.31	5990	610	41700	4250	0.84	6.41	4960	506	41700	4250	1.01	5	8185DB	273				
			59000	6010					59000	6010								
			84100	8570					84100	8570								
			84100	8570					84100	8570								
			104000	10600					104000	10600								
			145000	14800					139000	14100								
			145000	14800					139000	14100								
4.55	5000	510	41700	4250	*	5.49	5000	510	41700	4250	*	5	8185DB	319				
	7000	713	59000	6010			59000	6010										
			84100	8570			84100	8570										
			84100	8570			84100	8570										
			104000	10600			104000	10600										
			145000	14800			144000	14700										
			179000	18200			179000	18200										
3.85	8270	843	58900	6010	0.96	4.64	6850	698	59000	6010	1.16	5	8195DA	377				
			84100	8570					84100	8570								
			84100	8570					84100	8570								
			104000	10600					104000	10600								
			145000	14800					145000	14800								
			179000	18200					179000	18200								
3.07	7960	811	59000	6010	*	3.70	7960	811	59000	6010	*	5	8195DA	473				
	10400	1060	84100	8570			84100	8570										
			84100	8570			84100	8570										
			104000	10600			104000	10600										
			145000	14800			145000	14800										
			179000	18200			179000	18200										
			208000	21200			208000	21200										
2.94	7960	811	59000	6010	*	3.55	7960	811	59000	6010	*	5	8195DA	493				
	9230	941	84100	8570			84100	8570										
	10800	1100	84100	8570			84100	8570										
			104000	10600			104000	10600										
			145000	14800			145000	14800										
			179000	18200			179000	18200										
			208000	21200			208000	21200										
2.59	12300	1250	104000	10600	1.03	3.13	10200	1040	104000	10600	1.25	5	8215DA	559				
			145000	14800					145000	14800								
			179000	18200					179000	18200								
			208000	21200					208000	21200								
			258000	26300					258000	26300								
2.23	14200	1450	104000	10600	0.89	2.70	11800	1200	104000	10600	1.07	5	8215DA	649				
			145000	14800					145000	14800								
			179000	18200					179000	18200								
			208000	21200					208000	21200								
			258000	26300					258000	26300								

3.7 kW 5 HP	Hz	50Hz		60Hz	
	Pole	4	6	4	6
	n ₁	1450	980	1750	1165

50Hz						60Hz						Model 型號			Dimension Page 頁數						
Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Input Capacity Symbol 馬力 編號	Frame Size 框號	Ratio 速比	HM	VM	H	V			
	N.m	Kgf.m	N	kgf			N.m	Kgf.m	N	kgf											
1.98	12700	1290	104000	10600	*	2.39	12700	1290	104000	10600	*	5	8215DA	731							
			145000	14800	1.00				145000	14800	1.20										
	179000	18200	1.28	13300	1350		179000	18200	1.54	5	8235DA								731		
	208000	21200	1.61				208000	21200	1.94	5	8245DA								731		
	258000	26300	2.15				258000	26300	2.60	5	8255DA								731		
1.72	18400	18800	145000	14800	0.82	2.08	15300	1560	145000	14800	0.98	5	8225DA	841							
			179000	18200	1.02				179000	18200	1.24								5	8235DA	841
			208000	21200	1.40				208000	21200	1.69								5	8245DA	841
			258000	26300	1.76				258000	26300	2.13								5	8255DA	841
			145000	14800	*				1.74	15900	1620								145000	14800	*
179000	18200	0.93	179000	18200	1.12	5	8235DA	1003													
208000	21200	1.17	208000	21200	1.42	5	8245DA	1003													
258000	26300	1.57	258000	26300	1.89	5	8255DA	1003													
1.16	20500	2090	179000	18200	*	1.40	20500	2090	179000	18200	*	5	8235DA	1247							
			208000	21200	0.94				208000	21200	1.14								5	8245DA	1247
	27300	2790	258000	26300	1.26		22700	2310	258000	26300	1.52								5	8255DA	1247
0.980	22600	2310	208000	21200	*	1.18	22600	2310	208000	21200	*	5	8245DA	1479							
	32400	3310	258000	26300	0.96		26900	2740	258000	26300	1.15								5	8255DA	1479
0.784	40600	4130	258000	26300	0.85	0.946	33600	3430	258000	26300	1.03	5	8255DA	1849							
0.702	34500	3520	258000	26300	*	0.847	34500	3520	258000	26300	*	5	8255DA	2065							
0.572	34500	3520	258000	26300	*	0.690	34500	3520	258000	26300	*	5	8255DA	2537							
0.476	31000	3160	258000	26300	*	0.575	31000	3160	258000	26300	*	5	8255DA	3045							
0.417	34500	3520	258000	26300	*	0.503	34500	3520	258000	26300	*	5	8255DA	3481							
0.327	31000	3160	258000	26300	*	0.394	31000	3160	258000	26300	*	5	8255DA	4437							
0.282	34500	3520	258000	26300	*	0.341	34500	3520	258000	26300	*	5	8255DA	5133							
0.235	31000	3160	258000	26300	*	0.283	31000	3160	258000	26300	*	5	8255DA	6177							
0.192	31000	3160	258000	26300	*	0.231	31000	3160	258000	26300	*	5	8255DA	7569							

5.5 kW 7½ HP	Hz	50Hz		60Hz	
	Pole	4	6	4	6
	n ₁	1450	980	1750	1165

50Hz						60Hz						Model 型號			Dimension Page 頁數			
Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Input Capacity Symbol 馬力 編號	Frame Size 框號	Ratio 速比	HM	VM	H	V
	N.m	Kgf.m	N	kgf			N.m	Kgf.m	N	Kgf								
242	206	21.0	6060	617	2.05	292	171	17.4	5710	582	2.05	8	8135	6				
			9370	955	2.75				8860	903	2.75							
181	275	28.1	6740	687	2.05	219	228	23.3	6360	648	2.05	8	8135	8				
			10400	1060	2.75				9820	1000	2.75							
132	379	38.6	7680	783	2.05	159	314	32.0	7240	739	2.05	8	8135	11				
			11600	1190	2.75				11000	1120	2.75							
112	447	45.6	7980	814	1.85	135	371	37.8	7530	768	2.05	8	8135	13				
			11900	1210	2.75				11300	1150	2.75							

5.5 kW 7½ HP	Hz	50Hz		60Hz	
	Pole	4	6	4	6
	n ₁	1450	980	1750	1165

50Hz					60Hz					Model 型號			Dimension Page 頁數					
Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Input Capacity Symbol 馬力 編號	Frame Size 框號	Ratio 速比	HM	VM	H	V
	N.m	Kgf.m	N	kgf			N.m	Kgf.m	N	Kgf								
96.7	516	52.6	8130	829	1.63	117	428	43.6	7680	783	1.63	8	8135	15				
			12400	1270	2.64				11800	1200	2.75		8	8145	15			
85.3	585	59.6	8710	888	1.51	103	485	49.4	8230	839	1.51	8	8135	17				
			13000	1320	2.18				12300	1250	2.18		8	8145	17			
			15300	1550	2.38				14400	1460	2.38		8	8165	17			
			9260	944	1.22				8760	893	1.37		8	8135	21			
69.0	723	73.7	13900	1410	1.73	83.3	599	61.0	13100	1340	2.00	8	8145	21				
			16400	1670	2.91				15400	1570	2.93		8	8165	21			
			9580	977	1.05				9070	925	1.08		8	8135	25			
58.0	860	87.7	14500	1480	1.44	70.0	713	72.7	13800	1400	1.44	8	8145	25				
			17100	1740	2.44				16100	1640	2.75		8	8165	25			
			19200	1960	2.84				18100	1840	2.87		8	8175	25			
			10000	1020	0.89				9500	968	1.03		8	8135	29			
50.0	998	102	14800	1510	1.37	60.3	827	84.3	14100	1430	1.37	8	8145	29				
			17800	1810	2.07				16800	1710	2.07		8	8165	29			
			20200	2060	2.45				19100	1940	2.60		8	8175	29			
			15900	1620	1.14				15000	1530	1.37		8	8145	35			
41.4	1200	123	18800	1920	1.74	50.0	998	102	17800	1810	2.07	8	8165	35				
			21400	2180	2.62				20200	2060	2.75		8	8175	35			
			15100	1540	0.85				15600	1590	0.98		8	8145	43			
33.7	1480	151	20000	2040	1.42	40.7	1230	125	18900	1930	1.44	8	8165	43				
			22800	2320	2.05				21500	2190	2.05		8	8175	43			
			30900	3150	2.75				29100	2960	2.75		8	8185	43			
			20800	2120	1.20				19600	2000	1.37		8	8165	51			
28.4	1760	179	23700	2420	1.79	34.3	1450	148	22400	2280	2.05	8	8175	51				
			31900	3260	2.75				30100	3070	2.75		8	8185	51			
			22100	2250	1.03				21700	2220	1.05		8	8165	59			
24.6	2030	207	24800	2530	1.51	29.7	1680	171	23400	2390	1.51	8	8175	59				
			33400	3400	2.18				31400	3200	2.18		8	8185	59			
			47000	4790	2.78				44200	4500	2.78		8	8195	59			
			22100	2250	0.86				21600	2200	1.03		8	8165	71			
20.4	2440	249	26200	2670	1.27	24.6	2020	206	24700	2520	1.30	8	8175	71				
			35500	3620	1.78				33400	3410	1.78		8	8185	71			
			49800	5080	2.84				46900	4780	2.84		8	8195	71			
			27900	2840	1.02				26400	2690	1.02		8	8175	87			
16.7	2990	305	38100	3880	1.56	20.1	2480	253	35900	3660	1.56	8	8185	87				
			53600	5470	2.47				50500	5140	2.47		8	8195	87			
			40500	4130	1.45				38200	3890	1.74		8	8185DB	104			
13.9	3390	346	56800	5790	2.17	16.8	2810	286	53500	5460	2.17	8	8195DB	104				
			41700	4250	1.22				40600	4140	1.47		8	8185DB	121			
			59000	6010	1.92				57000	5810	2.17		8	8195DB	121			
12.0	3940	402	84100	8570	2.17	14.5	3270	333	84100	8570	2.17	8	8205DB	121				
			104000	10600	2.88				103000	10500	3.48		8	8215DB	121			
			41700	4250	1.05				41700	4250	1.27		8	8185DB	143			
			59000	6010	1.64				59000	6010	1.97		8	8195DB	143			
10.1	4660	475	41700	4250	1.05	12.2	3860	394	41700	4250	1.27	8	8185DB	143				
			59000	6010	1.64				59000	6010	1.97		8	8195DB	143			
			41700	4250	0.92				41700	4250	1.10		8	8185DB	165			
			59000	6010	1.47				59000	6010	1.77		8	8195DB	165			
			84100	8570	1.72				84100	8570	2.08		8	8205DB	165			
			104000	10600	2.17				104000	10600	2.17		8	8215DA	165			
			104000	10600	2.26				104000	10600	2.73		8	8215DB	165			
124000	12700	2.69	118000	12000	3.25	8	8225DB	165										

5.5 kW 7½ HP	Hz	50Hz		60Hz	
	Pole	4	6	4	6
	n ₁	1450	980	1750	1165

50Hz					60Hz					Model 型號			Dimension Page 頁數					
Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out} N.m Kgf.m		Allowable Radial Load 應許徑向負載 Pro N kgf		SF	Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out} N.m Kgf.m		Allowable Radial Load 應許徑向負載 Pro N kgf		SF	Input Capacity Symbol 馬力 編號	Frame Size 框號	Ratio 速比	HM	VM	H	V
	N.m	Kgf.m	N	kgf			N.m	Kgf.m	N	kgf								
7.44	6360	648	58900	6000	1.24	8.97	5270	537	59000	6010	1.50	8	8195DB	195				
			84100	8570	1.46				84100	8570	1.76		8205DB	195				
			104000	10600	1.91				104000	10600	2.17		8215DA	195				
			104000	10600	1.91				104000	10600	2.31		8215DB	195				
			131000	13300	1.96				124000	12600	2.17		8225DA	195				
			131000	13300	2.28				124000	12600	2.75		8225DB	195				
6.28	7530	768	59000	6010	1.06	7.58	6240	636	59000	6010	1.28	8	8195DB	231				
			84100	8570	1.23				84100	8570	1.49		8205DB	231				
			104000	10600	1.66				104000	10600	2.00		8215DA	231				
			139000	14200	1.97				132000	13400	2.17		8225DA	231				
			139000	14200	1.97				132000	13400	2.37		8225DB	231				
			173000	17700	2.51				164000	16700	3.03		8235DA	231				
5.31	8900	907	59000	6010	0.89	6.41	7370	752	59000	6010	1.08	8	8195DB	273				
			84100	8570	1.04				84100	8570	1.26		8205DB	273				
			104000	10600	1.40				104000	10600	1.70		8215DA	273				
			145000	14800	1.66				138000	14100	2.01		8225DA	273				
			179000	18200	2.12				172000	17600	2.56		8235DA	273				
			203000	20600	2.90				192000	19500	3.50		8245DA	273				
4.55	7960	811	59000	6010	*	5.49	7960	811	59000	6010	*	8	8195DB	319				
	10400	1060	84100	8570	0.89		8620	878	84100	8570	1.07		8205DB	319				
			104000	10600	1.22				104000	10600	1.47		8215DA	319				
			145000	14800	1.45				143000	14600	1.75		8225DA	319				
			179000	18200	1.82				179000	18200	2.19		8235DA	319				
			208000	21200	2.48				200000	20400	2.99		8245DA	319				
3.85	7960	811	59000	6010	*	4.64	7960	811	59000	6010	*	8	8195DB	377				
	8550	872	84100	8570	*		8030	819	84100	8570	*		8205DB	377				
	12300	1250	104000	10600	1.03		10200	1040	104000	10600	1.24		8205DB	377				
			145000	14800	1.22				145000	14800	1.48		8225DA	377				
			179000	18200	1.54				179000	18200	1.86		8235DA	377				
			208000	21200	2.10				208000	21200	2.53		8245DA	377				
258000	26300	2.64	258000	26300	3.19	8255DA	377											
3.07	15400	1570	104000	10600	0.82	3.70	12800	1300	104000	10600	0.98	8	8215DA	473				
			145000	14800	1.04				145000	14800	1.25		8225DA	473				
			179000	18200	1.33				179000	18200	1.60		8235DA	473				
			208000	21200	1.67				208000	21200	2.02		8245DA	473				
			258000	26300	2.24				258000	26300	2.70		8255DA	473				
			276000	28100	2.98				276000	28100	3.60		8265DA	473				
2.94	12700	1290	104000	10600	*	3.55	12700	1290	104000	10600	*	8	8215DA	493				
	16100	1640	145000	14800	0.93		13000	1350	145000	14800	1.13		8225DA	493				
			179000	18200	1.17				179000	18200	1.42		8235DA	493				
			208000	21200	1.60				208000	21200	1.94		8245DA	493				
			258000	26300	2.02				258000	26300	2.44		8255DA	493				
			276000	28100	2.86				276000	28100	3.46		8265DA	493				
2.59	18200	1860	145000	14800	0.88	3.13	15100	1540	145000	14800	1.06	8	8225DA	559				
			179000	18200	1.12				179000	18200	1.36		8235DA	559				
			208000	21200	1.42				208000	21200	1.71		8245DA	559				
			258000	26300	1.89				258000	26300	2.28		8255DA	559				
			276000	28100	2.52				276000	28100	3.05		8265DA	559				

5.5 kW 7½ HP	Hz	50Hz		60Hz	
	Pole	4	6	4	6
	n ₁	1450	980	1750	1165

50Hz						60Hz						Model 型號			Dimension Page 頁數				
Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Input Capacity Symbol 馬力 編號	Frame Size 框號	Ratio 速比	HM	VM	H	V	
	N.m	Kgf.m	N	kgf			N.m	Kgf.m	N	kgf									
2.23	15900	1620	145000	14800	*	2.70	15900	1620	145000	14800	*	8	8225DA	649					
			179000	18200	0.97				179000	18200	1.17		8235DA	649					
	21200	2160	208000	21200	1.22		17500	1790	208000	21200	1.47		8	5245DA	649				
			258000	26300	1.63				258000	26300	1.97		8	8255DA	649				
			276000	28100	2.17				276000	28100	2.62		8	8265DA	649				
1.98	16000	1630	145000	14800	*	2.39	16000	1630	145000	14800	*	8	8225DA	731					
			179000	18200	0.86				179000	18200	1.04		8	8235DA	731				
	23800	2430	208000	21200	1.08		19700	2010	208000	21200	1.31		8	8245DA	731				
			258000	26300	1.45				258000	26300	1.75		8	8255DA	731				
			276000	28100	1.93				276000	28100	2.33		8	8265DA	731				
1.72	18900	1930	179000	18200	*	2.08	18900	1930	179000	18200	*	8	8235DA	841					
			208000	21200	0.94				208000	21200	1.14		8	8245DA	841				
	27400	2790	258000	26300	1.18		22700	2320	258000	26300	1.43		8	8255DA	841				
			276000	28100	1.68				276000	28100	2.02		8	8265DA	841				
1.45	25800	2630	208000	21200	*	1.74	25800	2630	208000	21200	*	8	8245DA	1003					
			258000	26300	1.06				258000	26300	1.27		8	8255DA	1003				
	32700	3330	276000	28100	1.41		27100	2760	276000	28100	1.70		8	8265DA	1003				
1.16	25800	2630	208000	21200	*	1.40	25800	2630	208000	21200	*	8	8245DA	1247					
			258000	26300	0.85				258000	26300	1.02		8	8255DA	1247				
	40700	41400	276000	28100	1.13		33700	3430	276000	28100	1.37		8	8265DA	1247				
0.980	31000	3160	258000	26300	*	1.18	31000	3160	258000	26300	*	8	8255DA	1479					
			48200	4920	276000				28100	0.91	40000		4070	276000	28100	1.10	8	8265DA	1479
0.784	34500	3520	258000	26300	*	0.946	34500	3520	258000	26300	*	8	8255DA	1849					
			46000	4690	276000				28100	*	46000		4690	276000	28100	*	8	8265DA	1849
0.702	46000	4690	276000	28100	*	0.847	46000	4690	276000	28100	*	8	8265DA	2065					
0.572	46000	4690	276000	28100	*	0.690	46000	4690	276000	28100	*	8	8265DA	2537					
0.476	44000	4490	276000	28100	*	0.575	44000	4490	276000	28100	*	8	8265DA	3045					
0.417	46000	4690	276000	28100	*	0.503	46000	4690	276000	28100	*	8	8265DA	3481					
0.327	44000	4490	276000	28100	*	0.394	44000	4490	276000	28100	*	8	8265DA	4437					
0.282	46000	4690	276000	28100	*	0.341	46000	4690	276000	28100	*	8	8265DA	5133					
0.235	44000	4490	276000	28100	*	0.283	44000	4490	276000	28100	*	8	8265DA	6177					
0.192	44000	4490	276000	28100	*	0.231	44000	4490	276000	28100	*	8	8265DA	7569					

7.5 kW 10 HP	Hz	50Hz		60Hz	
	Pole	4	6	4	6
	n _r	1450	980	1750	1165

50Hz					60Hz					Model 型號			Dimension Page 頁數					
Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Input Capacity Symbol 馬力 編號	Frame Size 框號	Ratio 速比	HM	VM	H	V
	N.m	Kgf.m	N	kgf			N	kgf	N	kgf								
242	282	28.7	5980	610	1.51	292	233	23.8	5650	576	1.51	10	8135	6				
			9330	951	2.01				8830	901	2.01		8145	6				
			10400	1070	2.71				9830	1000	2.71		8165	6				
181	375	38.3	6650	678	1.51	219	311	31.7	6290	641	1.25	10	8135	8				
			10300	1050	2.01				9790	998	1.73		8145	8				
			11700	1190	2.63				11000	1120	2.63		8165	8				
132	516	52.6	7570	771	1.51	159	428	43.6	7150	729	1.51	10	8135	11				
			11600	1180	2.01				11000	1120	1.73		8145	11				
			13200	1350	2.63				12500	1270	2.63		8165	11				
112	610	62.2	7860	801	1.36	135	505	51.5	7430	758	1.25	10	8135	13				
			11800	1210	2.01				11200	1140	1.73		8145	13				
			13800	1410	2.63				13000	1330	2.63		8165	13				
96.7	704	71.8	8000	815	1.20	117	583	59.5	7570	771	1.20	10	8135	15				
			12400	1260	1.93				11700	1200	2.01		8145	15				
			14700	1490	2.99				13800	1410	3.01		8165	15				
85.3	798	81.3	8550	872	1.11	103	661	67.4	8100	826	1.11	10	8135	17				
			12900	1320	1.60				12200	1250	1.60		8145	17				
			15100	1540	2.51				14300	1450	2.51		8165	17				
			17100	1740	2.63				16100	1640	2.63		8175	17				
69.0	985	100	9050	923	0.90	83.3	817	83.2	8590	876	1.00	10	8135	21				
			13800	1410	1.27				13100	1330	1.47		8145	21				
			16200	1650	2.13				15300	1560	2.15		8165	21				
			18400	1880	2.48				17400	1770	2.60		8175	21				
58.0	1170	120	14400	1470	1.05	70.0	972	99.1	13700	1390	1.05	10	8145	25				
			16900	1720	1.79				15900	1630	2.01		8165	25				
			19100	1940	2.60				18000	1830	2.60		8175	25				
50.0	1360	139	14700	1500	1.00	60.3	1130	115	14000	1420	1.00	10	8145	29				
			17600	1790	1.52				16600	1690	1.52		8165	29				
			20100	2050	2.32				18900	1930	2.51		8175	29				
			26800	2740	2.60				25300	2580	2.60		8185	29				
41.4	1640	167	14500	1480	0.83	50.0	1360	139	14900	1520	1.00	10	8145	35				
			18600	1890	1.28				17500	1790	1.52		8165	35				
			21200	2160	1.92				20000	2040	2.01		8175	35				
			28600	2920	2.47				26900	2750	2.51		8185	35				
33.7	2020	206	19700	2010	1.04	40.7	1670	170	18600	1900	1.05	10	8165	43				
			22500	2300	1.51				21300	2170	1.51		8175	43				
			30700	3130	2.48				28900	2950	2.51		8185	43				
			42800	4370	2.79				40300	4110	2.79		8195	43				
28.4	2390	244	20400	2080	0.88	34.3	1980	202	19300	1970	1.00	10	8165	51				
			23400	2390	1.32				22100	2250	1.51		8175	51				
			31700	3230	2.01				29900	3050	2.01		8185	51				
			44800	4560	2.79				42100	4290	2.79		8195	51				
24.6	2770	282	24400	2490	1.11	29.7	2290	234	23100	2360	1.11	10	8175	59				
			33100	3380	1.30				31200	3180	1.60		8185	59				
			46800	4770	2.51				44000	4490	2.51		8195	59				
20.4	3330	340	25700	2620	0.93	24.6	2760	281	24300	2480	0.95	10	8175	71				
			35100	3580	1.31				33100	3380	1.31		8185	71				
			49600	5050	2.08				46700	4760	2.08		8195	71				
16.7	4080	416	37700	3840	1.15	20.1	3380	345	35600	3620	1.15	10	8185	87				
			53300	5430	1.81				50200	5120	1.81		8195	87				

11 kW 15 HP	Hz	50Hz		60Hz	
	Pole	4	6	4	6
	n ₁	1450	980	1750	1165

50Hz					60Hz					Model 型號			Dimension Page 頁數					
Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Input Capacity Symbol 馬力 編號	Frame Size 框號	Ratio 速比	HM	VM	H	V
	N.m	Kgf.m	N	kgf			N.m	Kgf.m	N	kgf								
242	413	42.1	10400	1060	2.19	292	342	34.9	9760	995	2.19	15	8165	6				
			11700	1190	2.74				11000	1120	2.74		15	8175	6			
181	551	56.1	11600	1180	2.19	219	456	46.5	10900	1110	2.19	15	8165	8				
			12900	1320	2.74				12200	1240	2.74		15	8175	8			
132	757	77.2	13100	1330	2.19	159	627	63.9	12300	1260	2.19	15	8165	11				
			14900	1520	2.74				14000	1430	2.74		15	8175	11			
112	895	91.2	13700	1390	2.05	135	741	75.6	12900	1320	2.05	15	8165	13				
			15500	1580	2.74				14600	1490	2.74		15	8175	13			
96.7	1030	105	14500	1470	2.04	117	855	87.2	13600	1390	2.05	15	8165	15				
			16300	1660	2.74				15400	1570	2.74		15	8175	15			
			21700	2210	2.95				20400	2080	2.95		15	8185	15			
85.3	1170	119	14900	1520	1.71	103	969	98.8	14100	1430	1.71	15	8165	17				
			16900	1720	2.19				16000	1630	2.19		15	8175	17			
			22900	2340	2.78				21600	2200	2.78		15	8185	17			
69.0	1450	147	15900	1620	1.45	83.3	1200	122	15000	1530	1.46	15	8165	21				
			18200	1860	2.15				17200	1750	2.19		15	8175	21			
			24500	2500	2.73				23100	2350	2.73		15	8185	21			
58.0	1720	175	16600	1690	1.22	70.0	1430	145	15700	1600	1.37	15	8165	25				
			18800	1920	1.77				17800	1810	1.77		15	8175	25			
			25500	2600	2.74				24000	2450	2.74		15	8185	25			
50.0	2000	203	17200	1750	1.04	60.3	1650	169	16300	1660	1.04	15	8165	29				
			19800	2010	1.58				18700	1900	1.71		15	8175	29			
			26600	2710	2.19				25100	2560	2.19		15	8185	29			
			37500	3830	2.79				35300	3600	2.79		15	8195	29			
41.4	2410	246	18100	1840	0.87	50.0	2000	203	17100	1750	1.04	15	8165	35				
			20900	2130	1.31				19700	2010	1.37		15	8175	35			
			28400	2890	2.05				26700	2730	2.05		15	8185	35			
			39600	4040	2.74				37300	3800	2.74		15	8195	35			
33.7	2960	302	22100	2250	1.03	40.7	2450	250	20900	2130	1.03	15	8175	43				
			30300	3090	1.69				28600	2920	1.71		15	8185	43			
			42600	4340	2.46				40100	4090	2.74		15	8195	43			
			77700	7920	2.89				73500	7500	2.89		15	8205	43			
28.4	3510	358	22900	2330	0.90	34.3	2910	296	21700	2210	1.03	15	8175	51				
			31300	3200	1.37				29600	3010	1.37		15	8185	51			
			44400	4530	1.90				41900	4270	1.90		15	8195	51			
24.6	4060	414	32700	3330	1.09	29.7	3360	343	30900	3150	1.09	15	8185	59				
			46400	4730	1.71				43700	4460	1.71		15	8195	59			
			84100	8570	2.05				79900	8150	2.05		15	8205	59			
20.4	4890	498	34500	3520	0.89	24.6	4050	413	32700	3330	0.89	15	8185	71				
			49100	5010	1.42				46300	4720	1.42		15	8195	71			
16.7	5990	610	52700	5380	1.24	20.1	4960	506	49700	5070	1.24	15	8195	87				
			84100	8570	1.45				84100	8570	1.45		15	8205	87			
			96600	9850	1.79				91500	9320	1.95		15	8215	87			
12.0	7890	804	104000	10600	1.44	14.5	6540	666	102000	10400	1.74	15	8215DB	121				
			114000	11600	1.71				108000	11000	2.06		15	8225DB	121			
			143000	14600	2.31				135000	13800	2.31		15	8235DA	121			
			143000	14600	2.37				135000	13800	2.86		15	8235DB	121			
			159000	16200	2.60				151000	15400	3.14		15	8245DB	121			
			195000	19900	2.89				184000	18800	2.89		15	8255DA	121			

11 kW 15 HP	Hz	50Hz		60Hz	
	Pole	4	6	4	6
	n ₁	1450	980	1750	1165

50Hz						60Hz						Model 型號			Dimension Page 頁數			
Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Input Capacity Symbol 馬力 編號	Frame Size 框號	Ratio 速比	HM	VM	H	V
	N.m	Kgf.m	N	kgf			N	kgf	N	kgf								
1.98	34500	3520	258000	26300	*	2.39	34500	3520	258000	26300	*	15	8255DA	731				
	47700	4860	276000	28100	0.97		39500	4030	276000	28100	1.16	15	8265DA	731				
			248000	25300	1.43				248000	25300	1.73	15	8275DA	731				
1.72	32500	3310	258000	26300	*	2.08	32500	3310	258000	26300	*	15	8255DA	841				
	54800	5590	276000	28100	0.84		45400	4630	276000	28100	1.01	15	8265DA	841				
			248000	25300	1.24				248000	25300	1.50	15	8275DA	841				
1.45	46000	4690	276000	28100	*	1.74	46000	4690	276000	28100	*	15	8265DA	1003				
	65400	6670	248000	25300	1.04		54200	5520	248000	25300	1.26	15	8275DA	1003				
1.16	81300	8290	248000	25300	0.84	1.40	67400	6870	248000	25300	1.01	15	8275DA	1247				
0.980	68200	6950	245000	25000	*	1.18	68200	6950	245000	25000	*	15	8275DA	1479				

15 kW 20 HP	Hz	50Hz		60Hz	
	Pole	4	6	4	6
	n ₁	1450	980	1750	1165

50Hz						60Hz						Model 型號			Dimension Page 頁數			
Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Input Capacity Symbol 馬力 編號	Frame Size 框號	Ratio 速比	HM	VM	H	V
	N.m	Kgf.m	N	kgf			N	kgf	N	kgf								
242	563	57.4	10200	1040	1.61	292	467	47.6	9670	986	1.61	20	8165	6				
			11600	1180	2.01				10900	1110	2.01	20	8175	6				
181	751	76.5	11400	1170	1.61	219	622	63.4	10800	1100	1.61	20	8165	8				
			12800	1310	2.01				12100	1230	2.01	20	8175	8				
132	1030	105	12900	1320	1.61	159	855	87.2	12200	1240	1.61	20	8165	11				
			14700	1500	2.01				13900	1420	2.01	20	8175	11				
			19600	2000	2.60				18500	1880	2.60	20	8185	11				
			27500	2800	2.73				25800	2630	2.73	20	8195	11				
112	1220	124	13500	1370	1.51	135	1010	103	12700	1300	1.31	20	8165	13				
			15300	1560	2.01				14500	1470	2.01	20	8175	13				
			20400	2080	2.60				19200	1960	2.60	20	8185	13				
			28600	2910	2.73				26900	2740	2.73	20	8195	13				
96.7	1410	144	14200	1450	1.49	117	1170	119	13500	1370	1.25	20	8165	15				
			16100	1640	2.01				15200	1550	2.01	20	8175	15				
			21600	2200	2.60				20300	2070	2.60	20	8185	15				
			30000	3060	2.73				28200	2880	2.73	20	8195	15				
85.3	1600	163	14600	1490	1.25	103	1320	135	13900	1410	1.25	20	8165	17				
			16700	1700	1.61				15800	1610	1.61	20	8175	17				
			22700	2320	2.55				21400	2180	2.60	20	8185	17				
			31600	3220	2.73				29800	3030	2.73	20	8195	17				
69.0	1970	201	15600	1590	1.07	83.3	1630	166	14800	1510	1.07	20	8165	21				
			17900	1830	1.57				17000	1730	1.61	20	8175	21				
			24300	2480	2.54				22900	2340	2.60	20	8185	21				
			34000	3470	2.73				32000	3260	2.73	20	8195	21				

15 kW 20 HP	Hz	50Hz		60Hz	
	Pole	4	6	4	6
	n ₁	1450	980	1750	1165

50Hz					60Hz					Model 型號			Dimension Page 頁數					
Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Input Capacity Symbol 馬力 編號	Frame Size 框號	Ratio 速比	HM	VM	H	V
	N.m	Kgf.m	N	kgf			N.m	Kgf.m	N	kgf								
58.0	2350	239	16200	1650	0.89	70.0	1940	198	15400	1570	1.01	20	8165	25				
			18500	1890	1.30				17500	1780	1.30		8175	25				
			25300	2580	2.01				23800	2430	2.01		8185	25				
			35600	3620	2.70				33500	3410	2.70		8195	25				
50.0	2720	277	19400	1980	1.16	60.3	2260	230	18400	1870	1.25	20	8175	29				
			26400	2690	1.61				24900	2540	1.61		8185	29				
			37400	3810	2.52				35200	3580	2.52		8195	29				
41.4	3280	335	20400	2080	0.96	50.0	2720	277	19400	1970	1.01	20	8175	35				
			28100	2860	1.51				26500	2700	1.51		8185	35				
			39400	4020	2.01				37100	3780	2.01		8195	35				
33.7	4040	411	29900	3050	1.24	40.7	3340	341	28300	2880	1.01	20	8185	43				
			42300	4310	1.81				39900	4060	1.39		8195	43				
			77500	7900	2.12				73300	7480	2.12		8205	43				
28.4	4790	488	30900	3150	1.01	34.3	3970	404	29200	2980	1.01	20	8185	51				
			44100	4490	1.39				41500	4230	1.39		8195	51				
24.6	5540	564	32100	3270	0.80	29.7	4590	468	30400	3100	0.80	20	8185	59				
			46000	4690	1.25				43400	4430	1.25		8195	59				
			84100	8570	1.51				79700	8120	1.51		8205	59				
			85900	8760	2.26				81300	8290	2.51		8215	59				
20.4	6660	679	48600	4960	1.04	24.6	5520	563	45900	4680	1.04	20	8195	71				
16.7	8170	832	52100	5310	0.91	20.1	6770	690	49200	5010	0.91	20	8195	87				
			84100	8570	1.06				84100	8570	1.06		8205	87				
			96100	9790	1.31				91000	9280	1.43		8215	87				
			102000	10400	1.78				96400	9830	1.78		8225	87				
			84100	8570	1.13				84100	8570	1.30		206	8205	59			
16.6	8190	835	96200	9800	1.55	19.7	6890	703	91500	9330	1.83	206	8215	59				
			102000	10400	1.94				97000	9890	2.22		8225	59				
			104000	10600	1.06				101000	10300	1.28		20	8215DB	121			
12.0	10800	1100	113000	11600	1.25	14.5	8910	909	108000	11000	1.51	20	8225DB	121				
			142000	14500	1.69				135000	13800	1.69		8235DA	121				
			142000	14500	1.74				135000	13800	2.10		8235DB	121				
			159000	16200	1.91				150000	15300	2.30		8245DB	121				
			194000	19800	2.12				184000	18700	2.12		8255DA	121				
			194000	19800	2.56				184000	18700	3.08		8255DB	121				
			237000	24200	2.91				225000	22900	3.38		8265DA	121				
			114000	11600	1.25				108000	11000	1.48		206	8225	87			
142000	14500	1.42	135000	13800	1.60	206	8235	87										
159000	16200	1.87	151000	15400	2.14	206	8245	87										
8.79	14700	1500	104000	10600	0.83	10.6	12200	1240	104000	10600	1.00	20	8215DB	165				
			122000	12500	0.98				116000	11800	1.19		8225DB	165				
			152000	15500	1.34				144000	14700	1.61		8235DA	165				
			170000	17400	1.69				161000	16400	1.69		8245DA	165				
			170000	17400	1.79				161000	16400	2.16		8245DB	165				
			209000	21300	2.12				197000	20100	2.12		8255DA	165				
			209000	21300	2.12				197000	20100	2.56		8255DB	165				
			254000	25900	2.98				241000	24500	3.38		8265DA	165				

18.5 kW 25 HP	Hz	50Hz		60Hz	
	Pole	4	6	4	6
	n ₁	1450	980	1750	1165

50Hz						60Hz						Model 型號			Dimension Page 頁數			
Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out} N.m Kgf.m		Allowable Radial Load 應許徑向負載 Pro N kgf		SF	Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out} N.m Kgf.m		Allowable Radial Load 應許徑向負載 Pro N kgf		SF	Input Capacity Symbol 馬力 編號	Frame Size 框號	Ratio 速比	HM	VM	H	V
11.3	14900	1520	113000	11500	1.01	13.4	12500	1280	108000	11000	1.20	256	8225	87				
			142000	14400	1.15				135000	13700	1.30	256	8235	87				
			159000	16200	1.52				151000	15400	1.74	256	8245	87				
			195000	19900	2.08				186000	18900	2.32	256	8255	87				
8.79	18100	1840	121000	12400	0.80	10.6	15000	1530	115000	11800	0.97	25	8225DB	165				
			151000	15400	1.08				144000	14600	1.31	25	8235DB	165				
			170000	17300	1.45				161000	16400	1.75	25	8245DB	165				
			208000	21200	1.72				197000	20100	2.08	25	8255DB	165				
			254000	25900	2.42				240000	24500	2.74	25	8265DA	165				
7.44	21400	2180	178000	18100	1.23	8.97	17700	1810	169000	17200	1.48	25	8245DB	195				
			218000	22200	1.46				207000	21100	1.76	25	8255DB	195				
			267000	27200	2.05				252000	25700	2.47	25	8265DA	195				
6.28	25300	2580	189000	19300	1.02	7.58	21000	2140	180000	18300	1.23	25	8245DB	231				
			232000	23600	1.22				219000	22400	1.48	25	8255DA	231				
			276000	28100	1.82				269000	27400	2.19	25	8265DA	231				
5.31	29900	3050	198000	20200	0.86	6.41	24800	2530	188000	19200	1.04	25	8245DB	273				
			243000	24800	1.04				230000	23500	1.25	25	8255DA	273				
			276000	28100	1.54				276000	28100	1.85	25	8265DA	273				
4.55	35000	3570	255000	26000	0.93	5.49	29000	2950	242000	24600	1.12	25	8255DB	319				
			276000	28100	1.31				276000	28100	1.59	25	8265DA	319				
			248000	25300	1.95				248000	25300	2.35	25	8275DA	319				
3.85	41300	4210	276000	28100	1.11	4.64	34300	3490	276000	28100	1.34	25	8265DA	377				
			248000	25300	1.65				248000	25300	1.99	25	8275DA	377				
3.07	51900	5290	276000	28100	0.89	3.70	43000	4380	276000	28100	1.07	25	8265DA	473				
			248000	25300	1.31				248000	25300	1.59	25	8275DA	473				
2.94	54100	5510	276000	28100	0.85	3.55	44800	4570	276000	28100	1.03	25	8265DA	493				
			248000	25300	1.26				248000	25300	1.52	25	8275DA	493				
2.59	61300	6250	248000	25300	1.11	3.13	50800	5180	248000	25300	1.34	25	8275DA	559				
2.23	71200	7250	248000	25300	0.96	2.70	59000	6010	248000	25300	1.16	25	8275DA	649				
1.98	80200	8170	248000	25300	0.85	2.39	66400	6770	248000	25300	1.03	25	8275DA	731				
1.72	68200	6950	248000	25300	*	2.08	68200	6950	248000	25300	*	25	8275DA	841				

22 kW 30 HP	Hz	50Hz		60Hz	
	Pole	4	6	4	6
	n ₁	1450	980	1750	1165

50Hz					60Hz					Model 型號			Dimension Page 頁數					
Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out} N.m Kgf.m		Allowable Radial Load 應許徑向負載 Pro N kgf		SF	Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out} N.m Kgf.m		Allowable Radial Load 應許徑向負載 Pro N kgf		SF	Input Capacity Symbol 馬力 編號	Frame Size 框號	Ratio 速比	HM	VM	H	V
	N.m	Kgf.m	N	kgf			N.m	Kgf.m	N	kgf								
12.0	15800	1610	112000	11400	0.85	14.5	13100	1330	106000	10900	1.03	30	8225DB	121				
			141000	14400	1.19				134000	13700	1.43		8235DB	121				
			157000	16000	1.30				149000	15200	1.57		8245DB	121				
			193000	19700	1.74				183000	18700	2.10		8255DB	121				
			237000	24100	1.99				224000	22800	2.31		8265DA	121				
11.3	17700	1810	158000	16100	1.28	13.4	14900	1520	150000	15300	1.46	306	8245	87				
			195000	19800	1.75				185000	18900	1.95		8255	87				
			237000	24200	2.43				226000	23000	2.43		8265	87				
8.79	21500	2190	151000	15400	0.91	10.6	17800	1820	143000	14600	1.10	30	8235DB	165				
			169000	17200	1.22				160000	16300	1.47		8245DB	165				
			207000	21100	1.45				196000	20000	1.45		8255DA	165				
			207000	21100	1.45				196000	20000	1.75		8255DB	165				
			253000	25800	2.03				240000	24400	2.31		8265DA	165				
7.44	25400	2590	177000	18000	1.03	8.97	21100	2150	168000	17100	1.25	30	8245DB	195				
			218000	22200	1.23				206000	21000	1.45		8255DA	195				
			218000	22200	1.23				206000	21000	1.48		8255DB	195				
			266000	27100	1.72				252000	25700	2.08		8265DA	195				
6.28	30100	3070	188000	19200	0.86	7.58	25200	2540	179000	18200	1.03	30	8245DB	231				
			231000	23500	1.03				219000	22300	1.24		8255DA	231				
			276000	28100	1.53				268000	27300	1.84		8265DA	231				
5.31	25800	2630	199000	20300	*	6.41	25800	2630	188000	19200	*	30	8245DB	273				
			242000	24700	0.87				229000	23400	1.05		8255DA	273				
			276000	28100	1.29				276000	28100	1.56		8265DA	273				
4.55	32500	3310	255000	26000	*	5.49	32500	3310	241000	24600	*	30	8255DA	319				
			276000	28100	1.11				276000	28100	1.33		8265DA	319				
3.85	49200	5010	276000	28100	0.94	4.64	40700	4150	248000	25300	1.98	30	8275DA	319				
			248000	25300	1.39				276000	28100	1.13		8265DA	377				
3.07	46000	4690	276000	28100	*	3.70	46000	4690	276000	28100	*	30	8265DA	473				
			61700	6290	1.11				51100	5210	1.33		8275DA	473				
2.94	46000	4690	276000	28100	*	3.55	46000	4690	276000	28100	*	30	8265DA	493				
			64300	6550	1.06				53300	5430	1.28		8275DA	493				
2.59	72900	7430	248000	25300	0.94	3.13	60400	6160	248000	25300	1.13	30	8275DA	559				
2.23	84600	8630	248000	25300	0.81	2.70	70100	7150	248000	25300	0.97	30	8275DA	649				
1.98	68200	6950	248000	25300	*	2.39	68200	6950	248000	25300	*	30	8275DA	731				

30 kW 40 HP	Hz	50Hz		60Hz	
	Pole	4	6	4	6
	n ₁	1450	980	1750	1165

50Hz						60Hz						Model 型號			Dimension Page 頁數			
Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Input Capacity Symbol 馬力 編號	Frame Size 框號	Ratio 速比	HM	VM	H	V
	N.m	Kgf.m	N	kgf			N.m	Kgf.m	N	Kgf								
12.0	13500	1370	113000	11500	*	14.5	13500	1370	106000	10800	*	40	8225DB	121				
			140000	14300	0.87				133000	13500	1.05							
	156000	15900	0.95	148000	15100		1.15											
	192000	19600	1.06	182000	18600		1.06											
	192000	19600	1.28	182000	18600		1.54											
	236000	24000	1.46	223000	22700		1.69											
11.3	24200	2460	193000	19700	1.28	13.4	20300	2070	184000	18800	1.43	406	8255	87				
			236000	24100	1.78				225000	22900	1.78							
8.79	19600	2000	151000	15400	*	10.6	19600	2000	143000	14500	*	40	8235DB	165				
			167000	17000	0.89				159000	16200	1.08							
	206000	21000	1.06	195000	19900		1.06											
	206000	21000	1.06	195000	19900		1.28											
	252000	25700	1.49	239000	24300		1.69											
7.75	26700	2720	218000	22200	*	9.4	221400	2250	207000	21100	*	40	8255DA	187				
			217000	22100	0.83				206000	21000	1.00							
	267000	27200	0.94	276000	28100		1.13											
7.44	26200	2680	177000	18000	*	8.97	26200	2680	167000	17000	*	40	8245DB	195				
			216000	22000	0.90				205000	20900	1.06							
	216000	22000	0.90	205000	20900		1.08											
	265000	27000	1.26	251000	25600		1.52											
6.28	25800	2630	189000	19300	*	7.58	25800	2630	179000	18200	*	40	8245DB	231				
			231000	23500	*				31000	3160	218000							
	41100	4190	276000	28100	1.12		34000	3470	267000	27200	1.35							
5.31	31000	3160	243000	24700	*	6.41	31000	3160	229000	23400	*	40	8255DA	273				
			276000	28100	0.95				40200	4100	276000							
4.55	56700	5780	276000	28100	0.81	5.49	47000	4790	276000	28100	0.98	40	8265DA	319				
			248000	25300	1.20				248000	25300	1.45							
3.85	46000	4690	276000	28100	*	4.64	46000	4690	276000	28100	*	40	8265DA	377				
			248000	25300	1.02				55500	5660	248000							
3.07	84100	8570	248000	25300	0.81	3.70	69700	7100	248000	25300	0.98	40	8275DA	473				
2.94	68200	6950	248000	25300	*	3.55	68200	6950	248000	25300	*	40	8275DA	493				
2.59	68200	6950	248000	25300	*	3.13	68200	6950	248000	25300	*	40	8275DA	559				

45 kW 60 HP	Hz	50Hz		60Hz	
	Pole	4	6	4	6
	n ₁	1450	980	1750	1165

50Hz					60Hz					Model 型號			Dimension Page 頁數							
Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Input Capacity Symbol 馬力編號	Frame Size 框號	Ratio 速比	HM	VM	H	V		
	N.m	Kgf.m	N	kgf			N.m	Kgf.m	N	kgf										
132	3100	316	51900	5290	1.33	159	2570	262	49200	5010	1.33	60	8205	11						
			52600	5360	1.67				49800	5080	1.67								8215	11
			55800	5690	2.21				52800	5390	2.21								8225	11
96.7	4220	431	55700	5680	1.33	117	3500	757	52800	5380	1.33	60	8205	15						
			56500	5750	1.67				53500	5450	1.67								8215	15
			60200	6140	2.21				57000	5820	2.21								8225	15
69.0	5910	603	62200	6340	1.32	83.3	4900	499	59000	6010	1.32	60	8205	21						
			63600	6480	1.67				60300	6140	1.67								8215	21
			67200	6850	2.09				63700	6490	2.09								8225	21
65.3	6250	637	62300	6350	1.33	77.7	5260	536	59300	6050	1.33	606	8205	15						
			63100	6430	1.67				60100	6130	1.67								8215	15
			67400	6870	2.21				64200	6540	2.21								8225	15
50.0	8170	832	67600	6890	1.02	60.3	6770	690	64100	6530	1.02	60	8205	29						
			68900	7030	1.30				65400	6660	1.30								8215	29
			73100	7450	1.67				69300	7070	1.67								8225	29
46.7	8750	892	69500	7080	1.06	55.5	7360	750	66200	6750	1.22	606	8205	21						
			71000	7240	1.43				67700	6900	1.67								8215	21
			75100	7660	1.69				71500	7290	2.01								8225	21
			94100	9590	2.16				89500	9130	2.17								8235	21
33.8	12100	1230	76800	7830	1.05	40.2	10200	1040	73200	7460	1.24	606	8215	29						
			81500	8310	1.24				77700	7920	1.48								8225	29
			102000	10400	1.56				97500	9940	1.67								8235	29
			114000	11700	2.09				109000	11100	2.09								8245	29
33.7	12100	1230	77200	7870	1.00	40.7	10000	1020	73300	7470	1.00	60	8215	43						
			82000	8360	1.26				77800	7940	1.26								8225	43
22.8	17900	1830	114000	11600	1.06	27.1	15100	1540	108000	11100	1.21	606	8235	43						
			128000	13100	1.44				122000	12400	1.67								8245	43
			157000	16000	1.73				150000	15300	1.98								8255	43
			193000	19700	2.51				184000	18700	2.51								8265	43
16.6	24600	25100	139000	14100	1.05	19.7	20700	2110	132000	13500	1.25	606	8245	59						
			210000	21400	1.87				200000	20400	2.09								8265	59
12.0	32300	3290	234000	23800	0.97	14.5	26700	2730	222000	22600	1.03	60	8265DA	121						
11.3	36200	3690	235000	23900	1.19	13.4	30500	3110	223000	22800	1.19	60	8265DA	87						
8.79	44000	4490	250000	25500	0.98	10.6	36500	3720	237000	24200	1.13	60	8265DA	165						
7.44	52000	5300	262000	26700	0.84	8.97	43100	4390	248000	25300	1.01	60	8265DA	195						
6.28	46000	4690	276000	28100	*	7.58	46000	4690	265000	27000	*	60	8265DA	231						
4.55	85100	8670	248000	25300	0.80	5.49	70500	7190	248000	25300	0.97	60	8275DA	319						

75 kW 100 HP	Hz	50Hz	60Hz
	Pole	6	6
	n ₁	980	1165

50Hz					60Hz					Model 型號			Dimension Page 頁數								
Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out} N.m Kgf.m		Allowable Radial Load 應許徑向負載 Pro N kgf		SF	Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out} N.m Kgf.m		Allowable Radial Load 應許徑向負載 Pro N kgf		SF	Input Capacity Symbol 馬力 編號	Frame Size 框號	Ratio 速比	HM	VM	H	V			
	N.m	Kgf.m	N	kgf			N.m	Kgf.m	N	kgf											
33.8	20100	2050	113000	11500	1.26	40.2	16900	1730	108000	11000	1.26	1006	8245	29							
			139000	14200	1.57				133000	13500	1.57								1006	8255	29
			172000	17500	2.12				163000	16600	2.12								1006	8265	29
22.8	29900	3040	155000	15800	1.04	27.1	25100	2560	148000	15100	1.19	1006	8255	43							
			191000	19500	1.51				182000	18600	1.51								1006	8265	43
			248000	25300	2.01				248000	25300	2.01								1006	8275	43
16.6	41000	4180	208000	21200	1.12	19.7	34500	3510	198000	20200	1.26	1006	8265	59							
			248000	25300	1.67				248000	25300	1.76								1006	8275	59

90 kW 125 HP	Hz	50Hz	60Hz
	Pole	6	6
	n ₁	980	1165

50Hz					60Hz					Model 型號			Dimension Page 頁數								
Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out} N.m Kgf.m		Allowable Radial Load 應許徑向負載 Pro N kgf		SF	Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out} N.m Kgf.m		Allowable Radial Load 應許徑向負載 Pro N kgf		SF	Input Capacity Symbol 馬力 編號	Frame Size 框號	Ratio 速比	HM	VM	H	V			
	N.m	Kgf.m	N	kgf			N.m	Kgf.m	N	kgf											
89.1	9170	934	86100	8780	1.47	106	7710	786	82000	8360	1.47	1256	8245	11							
			106000	10800	1.68				101000	10300	1.68								1256	8255	11
			130000	13200	1.94				123000	12600	1.94								1256	8265	11
65.3	12500	1270	92300	9410	1.47	77.7	10500	1070	87900	8960	1.47	1256	8245	15							
			113000	11600	1.68				108000	11000	1.68								1256	8255	15
			139000	14100	1.94				132000	13400	1.94								1256	8265	15
46.7	17500	1780	103000	10500	1.33	55.5	14700	1500	98200	10000	1.33	1256	8245	21							
			126000	12900	1.68				120000	12300	1.68								1256	8255	21
			155000	15800	1.91				147000	15000	1.91								1256	8265	21
33.8	24200	2460	112000	11400	1.05	40.2	20300	2070	107000	10900	1.05	1256	8245	29							
			139000	14100	1.31				132000	13500	1.31								1256	8255	29
			171000	17400	1.77				163000	16600	1.77								1256	8265	29
22.8	35800	3650	190000	19400	1.26	27.1	30100	3070	181000	18500	1.26	1256	8265	43							
			248000	25300	1.68				248000	25300	1.68								1256	8275	43
16.6	49200	5010	248000	25300	1.39	19.7	41400	4220	248000	25300	1.47	1256	8275	59							

110 kW 150 HP	Hz	50Hz	60Hz
	Pole	6	6
	n ₁	980	1165

50Hz					60Hz					Model 型號			Dimension Page 頁數					
Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Input Capacity Symbol 馬力 編號	Frame Size 框號	Ratio 速比	HM	VM	H	V
	N.m	Kgf.m	N	kgf			N	kgf	N	kgf								
89.1	11200	1140	85700	8730	1.20	106	9420	961	81600	8320	1.20	1506	8245	11				
			105000	10700	1.37				100000	10200	1.37							
65.3	15300	1560	91700	9350	1.20	77.7	12800	1310	87500	8910	1.20	1506	8245	15				
			113000	11500	1.37				108000	11000	1.37							
46.7	21400	2180	102000	10400	1.09	55.5	18000	1830	97500	9945	1.09	1506	8245	21				
			126000	12800	1.37				120000	12200	1.37							
33.8	29500	3010	138000	14000	1.07	40.2	24800	2530	131000	13400	1.07	1506	8255	29				
			170000	17300	1.45				162000	16500	1.45							
22.8	43800	4460	189000	19300	1.03	27.1	36800	3750	180000	18400	1.03	1506	8265	43				

132 kW 175 HP	Hz	50Hz	60Hz
	Pole	6	6
	n ₁	980	1165

50Hz					60Hz					Model 型號			Dimension Page 頁數					
Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Output Speed 轉速 n ₂ r/min	Output Torque 扭矩 T _{out}		Allowable Radial Load 應許徑向負載 Pro		SF	Input Capacity Symbol 馬力 編號	Frame Size 框號	Ratio 速比	HM	VM	H	V
	N.m	Kgf.m	N	kgf			N	kgf	N	kgf								
89.1	13400	1370	105000	10700	1.14	106	11300	1150	99900	10200	1.14	1756	8255	11				
			129000	13100	1.33				123000	12500	1.33							
65.3	18300	1870	112000	11500	1.14	77.7	15400	1570	107000	10900	1.14	1756	8255	15				
			138000	14000	1.33				131000	13400	1.33							
46.7	25700	2620	125000	12700	1.14	55.5	21600	2200	119000	12100	1.14	1756	8255	21				
			154000	15700	1.30				146000	14900	1.30							
33.8	35400	3610	169000	17200	1.20	40.2	29800	3040	161000	16500	1.20	1756	8265	29				